



Answer Key - MN: Mining Engineering

| Q.No. | Session | Que.Type | Sec. Name | Key | Marks |
|-------|---------|----------|-----------|--------------------|-------|
| 1 | 3 | MCQ | GA | C | 1 |
| 2 | 3 | MCQ | GA | B | 1 |
| 3 | 3 | MCQ | GA | D | 1 |
| 4 | 3 | MCQ | GA | D | 1 |
| 5 | 3 | MCQ | GA | B | 1 |
| 6 | 3 | MCQ | GA | D | 2 |
| 7 | 3 | MCQ | GA | C | 2 |
| 8 | 3 | MCQ | GA | B | 2 |
| 9 | 3 | MCQ | GA | B | 2 |
| 10 | 3 | MCQ | GA | B | 2 |
| 1 | 3 | MCQ | MN | C | 1 |
| 2 | 3 | MCQ | MN | A | 1 |
| 3 | 3 | MCQ | MN | D | 1 |
| 4 | 3 | MCQ | MN | B | 1 |
| 5 | 3 | MCQ | MN | B | 1 |
| 6 | 3 | MCQ | MN | C | 1 |
| 7 | 3 | MCQ | MN | A | 1 |
| 8 | 3 | MCQ | MN | D | 1 |
| 9 | 3 | MCQ | MN | A | 1 |
| 10 | 3 | MCQ | MN | B | 1 |
| 11 | 3 | MCQ | MN | D | 1 |
| 12 | 3 | MCQ | MN | C | 1 |
| 13 | 3 | MCQ | MN | C | 1 |
| 14 | 3 | MCQ | MN | B | 1 |
| 15 | 3 | MCQ | MN | D | 1 |
| 16 | 3 | NAT | MN | 18.0 to 20.0 | 1 |
| 17 | 3 | NAT | MN | 2.9 to 3.1 | 1 |
| 18 | 3 | NAT | MN | 5.4 to 5.6 | 1 |
| 19 | 3 | NAT | MN | 0.120 to 0.125 | 1 |
| 20 | 3 | NAT | MN | 2.4 to 2.6 | 1 |
| 21 | 3 | NAT | MN | 51830.0 to 51850.0 | 1 |
| 22 | 3 | NAT | MN | 0.560 to 0.580 | 1 |
| 23 | 3 | NAT | MN | 2 to 2 | 1 |
| 24 | 3 | NAT | MN | 5990.0 to 6010.0 | 1 |
| 25 | 3 | NAT | MN | 0.32 to 0.34 | 1 |
| 26 | 3 | MCQ | MN | B | 2 |
| 27 | 3 | MCQ | MN | D | 2 |
| 28 | 3 | MCQ | MN | C | 2 |
| 29 | 3 | MCQ | MN | A | 2 |
| 30 | 3 | MCQ | MN | D | 2 |
| 31 | 3 | MCQ | MN | C | 2 |
| 32 | 3 | MCQ | MN | D | 2 |
| 33 | 3 | MCQ | MN | D | 2 |

| | | | | | |
|----|---|-----|----|------------------|---|
| 34 | 3 | NAT | MN | 0.530 to 0.550 | 2 |
| 35 | 3 | NAT | MN | 148.0 to 154.0 | 2 |
| 36 | 3 | NAT | MN | 385.0 to 410.0 | 2 |
| 37 | 3 | NAT | MN | -205.0 to -195.0 | 2 |
| 38 | 3 | NAT | MN | 22.00 to 25.00 | 2 |
| 39 | 3 | NAT | MN | 7.2 to 7.7 | 2 |
| 40 | 3 | NAT | MN | -1.255 to -1.165 | 2 |
| 41 | 3 | NAT | MN | 2380.0 to 2396.0 | 2 |
| 42 | 3 | NAT | MN | 2.10 to 2.45 | 2 |
| 43 | 3 | NAT | MN | 3360.0 to 3480.0 | 2 |
| 44 | 3 | NAT | MN | 71.0 to 72.0 | 2 |
| 45 | 3 | NAT | MN | 71.0 to 73.0 | 2 |
| 46 | 3 | NAT | MN | 87.0 to 89.0 | 2 |
| 47 | 3 | NAT | MN | 0.44 to 0.50 | 2 |
| 48 | 3 | NAT | MN | 100.4 to 100.6 | 2 |
| 49 | 3 | NAT | MN | 157.0 to 161.0 | 2 |
| 50 | 3 | NAT | MN | 248.0 to 252.0 | 2 |
| 51 | 3 | NAT | MN | 0.020 to 0.030 | 2 |
| 52 | 3 | NAT | MN | 67.00 to 69.00 | 2 |
| 53 | 3 | NAT | MN | 18 to 18 | 2 |
| 54 | 3 | NAT | MN | 7.70 to 7.95 | 2 |
| 55 | 3 | NAT | MN | 30.8 to 31.6 | 2 |